



Bobcat Pneumatic Tires

Bobcat Pneumatic Tires

	Part Number	Make	Quality	O.D. (in)	O.D. (mm)	Section Width (in)	Section Width (mm)	Rim Diameter (in)	Ply Rating	O. Width (in)	Tread Depth 32nds	Tread Depth mm	Max. Load (lbs @ psi)	Max. Load (kg @ kg/cm2)	Weight (lbs)	Weight (kg)
10 x 16.5	6730106	SSL	SVR	30.7	779.8	10	254	16.5	10	10.4	44	34.9	3500 @ 45	1588 @ 3.16	76	34
	6729900	SSL	HVY	30.4	772.9	10	254	16.5	10	10.8	27	21.4	3930 @ 55	1783 @ 3.87	50	22
	7101734	SSL	ST	30.4	772.9	10	254	16.5	8	10.6	19	15.1	3930 @ 55	1783 @ 3.87	46	21
	7108389*	SSL	TURF	26.8	680.7	10	254	15	6	8.5	17	13.5	2610 @ 45	1184 @ 3.16	34	15
12 x 16.5	6730108	SSL, AWS	SVR	32.6	828.0	12	304.8	16.5	12	12.1	44	34.9	4210 @ 40	1910 @ 2.81	85	39
	6729901	SSL, AWS	HVY	32.9	835.7	12	304.8	16.5	12	12.8	30	23.8	5355 @ 60	2429 @ 4.22	77	35
	6729897	SSL, AWS	ST	32.7	830.8	12	304.8	16.5	10	12.8	25	19.8	5350 @ 60	2427 @ 4.22	64	29
	6678044*	SSL, AWS	TURF	33.1	840.7	15.9	402.6	16.5	10	16.1	18	14.3	4730 @ 32	2145 @ 2.25	80	36
	6730109*	SSL, AWS	FLOAT	32.6	828.0	15.5	393.7	16.5	12	15.8	26	20.6	4990 @ 35	2263 @ 2.46	94	43
14 x 17.5	7139189	SSL	SVR	36.0	914.4	14	355.6	17.5	14	13.8	44	34.9	5260 @ 35	2386 @ 2.46	130	59
	6675541	SSL	HVY	35.9	911.9	14	355.6	17.5	14	13.6	25	19.8	8550 @ 80	3878 @ 5.62	102	46
	6667794	SSL	ST	36.9	937.3	14	355.6	17.5	10	14.0	24	19.1	6850 @ 55	3107 @ 3.87	92	42
8.5 x 12	6661602	SSL	HVY	22.6	574.0	8.5	215.9	12	6	8.3	19	15.1	1810 @ 50	821 @ 3.52	26	12
	7109709	SSL	TURF	22.6	574.0	8.5	215.9	12	8	8.3	12	9.5	1670 @ 44	758 @ 3.09	19	9
8.5 x 15	6661603	SSL	ST	26.7	678.2	8.5	215.9	15	6	8.7	20	15.9	2270 @ 50	1030 @ 3.52	33	15
5.7 x 12.5	7101730	SSL	ST	22.7	576.6	5.7	144.8	12	4	5.8	15	11.9	1455 @ 60	660 @ 4.22	15	7



Standard

Heavy

Severe

Super Float*

Turf*

*Aftermarket rims required for this tire. Standard factory rims will not be compatible with tire. Please see your local Bobcat Dealership for details.